

Always a class ahead

KWC GASTRO E – the premium stainless-steel solution for the catering industry.

True professional kitchens dazzle with fittings from the KWC GASTRO E line made of pure V4A stainless steel. This means a longer service life thanks to the acid and chloride resistance, higher hygiene standards, greater safety and sustainability – also thanks to the extremely robust material.

The KWC GASTRO E line range is extensive. The variants can be combined and expanded with extension elements for any application. Another highlight is the robust dish spray with swivelling faceplate for maximum ease of use.





KWC GASTRO E

Premium in every detail



Innovative operation

The faceplate can be angled by 45° with a simple flick of the wrist. Maximum convenience in the professional kitchen and a genuine innovation from the KWC brand.

Rewarding care

The dish spray can be shut off for cleaning. It features delayed closing for pressure shock damping, and a valve maintenance unit. This ensures that the tap can be reliably maintained, which in turn helps increase its service life.



KWC GASTRO E

Premium quality from Unterkulm

True top performance

The KWC high-performance cartridge impresses with an exceptionally high flow rate – premium in everyday life, quality for decades, made by KWC.






Easy cleaning

The dish spray can be dismantled to clean or replace the valve and spray individually.


Dual-jet all-rounder

The water-saving dish spray offers two jet types. The conical cleaning jet is ideal for gentle washing, the high-performance jet for heavy soiling. The faceplate is adjustable, which makes work easier and protects the spray hose.











SAP Nr. Artikel Nr.

stainless steel, A 300, flexible connection hoses 125565 24.561.044.700FL

GASTRO E Lever mixer - Commercial kitchen

- Lever mixer
- Swivel spout 360°
 - with adjustable gland
- Jet regulator
- OptimalSpace ample space for washing or working
- KWC Cartridge XL 46 High capacity
- with ceramic discs
- flow rate and temperature continuously variable
- temperature limitation
- \bullet Flexible connection hoses ½" with transition to ¾"
- Fastening by means of threaded sleeve 1 1/4"
- Mounting hole size ø42 mm
- To be ordered separately:
- Socket 100 mm Z.539.000.700 or 300 mm Z.539.001.700

Flow rate 32.4 l/min (3 bar) Acoustic group II



Artikel Nr. SAP Nr.


stainless steel, A 450, flexible connection hoses 125566 24.561.046.700FL

GASTRO E Lever mixer - Commercial kitchen

- Lever mixer
- Swivel spout 360°
- with adjustable gland
- Jet regulator
- OptimalSpace ample space for washing or working
- KWC Cartridge XL 46 High capacity
 - with ceramic discs
 - flow rate and temperature continuously variable
- temperature limitation
- \bullet Flexible connection hoses ½" with transition to ¾"
- Fastening by means of threaded sleeve 1 1/4"
- Mounting hole size ø42 mm
- To be ordered separately:
 Socket 100 mm Z.539.000.700 or 300 mm Z.539.001.700

Flow rate 32.4 l/min (3 bar) Acoustic group II















SAP Nr.

Artikel Nr.


stainless steel, A 200, B 270, flexible connection hoses **125567** 24.561.144.700FL

GASTRO E Lever mixer - Commercial kitchen

- Lever mixer
- stainless steel suspension spring
- TouchProtect anti-scald protection thanks to the "double skin" principle
- Intrinsically safe against backflow and cross flow
- Swivel spout
- with adjustable gland
- Jet regulator
- Pre-rinse spray
- with integrated delayed closing device to minimize water hammer
- with valve maintenance unit for cleaning
- SprayClean easy to clean and actively prevents limescale buildup
- SprayLock lockable jet spray
- PowerClean needle spray mode
- OptimalSpace ample space for washing or working
- KWC Cartridge XL 46 High capacity
- with ceramic discs
- flow rate and temperature continuously variable
- temperature limitation
- Flexible connection hoses ½" with transition to ¾"
- Fastening by means of threaded sleeve 1 1/4"
- Mounting hole size ø42 mm

Flow rate 27 I/min (3 bar) Spray: Flow rate 15 I/min (3 bar) Acoustic group II Spray: Acoustic group I















SAP Nr.

Artikel Nr.

stainless steel, A 300, B 370, flexible connection hoses **125568** 24.561.146.700FL

GASTRO E Lever mixer - Commercial kitchen


- Lever mixer
- Stainless steel suspension spring
- TouchProtect anti-scald protection thanks to the "double skin" principle
- Intrinsically safe against backflow and cross flow
- Swivel spout
 - with adjustable gland
- Jet regulator
- Pre-rinse spray
- with integrated delayed closing device to minimize water hammer
- with valve maintenance unit for cleaning
- SprayClean easy to clean and actively prevents limescale buildup
- SprayLock lockable jet spray
- PowerClean needle spray mode
- OptimalSpace ample space for washing or working
- KWC Cartridge XL 46 High capacity
- with ceramic discs
- flow rate and temperature continuously variable
- temperature limitation
- Flexible connection hoses ½" with transition to ¾"
- Fastening by means of threaded sleeve 1 1/4"
- Mounting hole size ø42 mm

Flow rate 27 I/min (3 bar) Spray: Flow rate 15 I/min (3 bar) Acoustic group II Spray: Acoustic group I









SAP Nr. Artikel Nr.

G ¾"

3600006994 Z.530.928.700

GASTRO Drip-Stop

- Drip-Stop Prevents residual spout flow
- Suitable for:
 - KWC GASTRO E

SAP Nr. Artikel Nr.


graphite gray, G 1/2°

539030 Z.539.030.145


GASTRO Pre-rinse spray

- Pre-rinse spray
- with integrated delayed closing device to minimize water hammer with valve maintenance unit for cleaning and swivelling sieve jet
- Connecting thread 1/2"









Artikel Nr. SAP Nr. chromeline 300061 300061

Outlet swivel limiter M 38 x 15

- Suitable for: KWC GASTRO
 - 2-handle and lever mixer
 - one hole / 2-hole + wall mixer 3/4" limitation individually adjustable


SAP Nr. Artikel Nr.

chromeline, G 1 1/4"


300019 300019

Preassembled socket 5/4 zu KWC

- Mounting hole size ø60.5 mmSuitable for:
- KWC GASTRO
- 2-handle and lever mixer
- One hole mixer







SAP Nr.	Artikel Nr.
stainless steel	
539000	Z.539.000.700

GASTRO E Socket 100 mm

- Socket 100 mm Suitable for: KWC GASTRO E

Artikel Nr. SAP Nr. stainless steel 539001 Z.539.001.700

GASTRO E Socket 300 mm

- Socket 300 mm
- Suitable for: KWC GASTRO E

