



KWC-No.

119599

chromeline, A 140, flexible connection hoses, without pop-up valve, mains receiver, Basic, with mixing

119601

chromeline, A 140, flexible connection hoses, without pop-up valve, battery, Basic, with mixing

- * Automatic controlled
- Dual infrared sensor A10
- * With mixing
- temperature limiter adjustable
- * EcoProtect - water-saving device
- * Basic: counter-sunk iqua-click
- * Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration
- 12- or 24-hour-hygiene flushing activatable

- * Fixed spout
- Neoperl® Cascade®
- * OptimalSpace - ample space for washing or working
- * Electrovalve
- * Flexible connection hoses 3/8"
- * Fastening by means of stud bolt M8 x 1
- * Mounting hole size 63.5 mm
- * Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 6 V
 - 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

Technical Data

| |
|-----------------------------|
| A_Spout_Spray |
| ATT-KWC-ABLAUFGARNITUR |
| ATT-KWC-EL_STEUERUNG |
| Connection |
| ATT-KWC-AUSLAUF |
| ATT-KWC-IQUA_CLICK |
| ATT-KWC-STROMVERSORGUNG |
| ATT-KWC-FARBCODE |
| Installation_type |
| Faucet_typ |
| Measure_Height |
| G_Acoustic_group |
| Projection_A |
| EnergyLabelCH |
| ATT-KWC-MASS-WASSERAUSTRITT |
| Material |

| |
|----------------------------|
| 5 l/min (3 bar) |
| ohne_Ablaufgarnitur |
| berührungslos |
| Flexible_Anschlusschläuche |
| fest |
| Basic, mit Mischung |
| Netz AP |
| chromeline |
| Standmontage |
| Elektronik |
| 186 |
| I |
| A140 |
| A |
| 152 |
| Mässing |

