

#### KWC-No.

**121505**  
 stainless steel, A 235, flexible connection hoses


- \* Lever mixer
- \* TouchProtect - anti-scald protection thanks to the "double skin" principle
- \* Pull-out spray
  - SprayClean - easy to clean and actively prevents limescale buildup
  - up to 700 mm pull-out length
  - SprayLock - lockable jet spray
  - PowerClean - needle spray mode, with automatic diverter reset
  - hose surface to fit faucet surface

- \* Hose guide, swivelling 130°
- \* EasyLock - a pull-out spray that easily slides back into place
- \* KWC cartridge L 39 - universal
  - with ceramic discs
  - flow rate and temperature continuously variable
  - temperature and flow rate limitation
- \* Flexible connection hoses 3/8"
- \* Fastening by means of threaded sleeve M33 x 1.5
- \* Mounting hole size ø35 mm

#### Technické údaje

ATT-KWC-A_AUSZUGBRAUSE_SIEB
ATT-KWC-A_AUSZUGBRAUSE_NORMAL
Connection
ATT-KWC-AUSLAUF
Handling
Kitchen_spray
ATT-KWC-FARBCODE
Installation_type
Faucet_typ
Measure_Height
G_Acoustic group
Projection_A
EnergyLabelCH
ATT-KWC-MASS-WASSERAUSTRITT
Materiál

13 l/min (3 bar)
12 l/min (3 bar)
Flexible_Anschlussschläuche
schwenkbar
topbedient
Auszugbrause
stainless steel
Standmontage
Hebelmischer
216
I
A235
C
154
ROSTFREIER_STAHL



#### Náhradní díly



#### Cartridge L 39 - universal

---

**536591**  
K.32.60.00

---