



#### KWC-No.

**121513**  
 stainless steel, A 230, flexible connection hoses

- \* Lever mixer
- \* TouchProtect - anti-scald protection thanks to the "double skin" principle
- \* Pull-out aerator
- Neoperl® Cascade®
- up to 700 mm pull-out length
- hose surface to fit faucet surface
- \* Hose guide, swivelling 130°

- \* EasyLock - a pull-out spray that easily slides back into place
- \* KWC cartridge L 39 - universal
- with ceramic discs
- flow rate and temperature continuously variable
- temperature and flow rate limitation
- \* Flexible connection hoses 3/8"
- \* Fastening by means of threaded sleeve M33 x 1.5
- \* Mounting hole size ø35 mm

#### Technické údaje

A_Spout_Spray
Connection
ATT-KWC-AUSLAUF
Handling
Kitchen_spray
ATT-KWC-FARBCODE
Installation_type
Faucet_typ
Measure_Height
G_Acoustic group
Projection_A
EnergyLabelCH
ATT-KWC-MASS-WASSERAUSTRITT
Material

12 l/min (3 bar)
Flexible_Anschlusschläuche
schwenkbar
topbedient
Auszugauslauf
stainless steel
Standmontage
Hebelmischer
199
I
A230
C
156
ROSTFREIER_STAHL



#### Náhradní díly



**KWC** INOX  
Lever mixer - Kitchen

**Modell-Linie: INOX | 10.271.103.700FL**  
Umyvadlové armatury | Hydraulické armatury



**Cartridge L 39 - universal**

---

**536591**  
K.32.60.00

---