



KWC ONO
Lever mixer - Kitchen - detachable

Modell-Linie: ONO | 10.151.053.700FL
Taps | Manual taps



KWC-No.

123114
stainless steel, A 220, flexible connection hoses

- * Lever mixer
- * Detachable for installation below windows - detached 55 mm
- * Surgical-grade hardened stainless steel lever
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Intrinsically safe against backflow
- * Pull-out spray
 - SprayClean - easy to clean and actively prevents limescale buildup
 - up to 700 mm pull-out length
- PowerClean - needle spray mode, with automatic diverter reset

- hose surface to fit faucet surface
- * Hose guide, swivelling 105°
- * EasyLock - a pull-out spray that easily slides back into place
- * KWC cartridge M 35 H
 - with ceramic discs
 - flow rate and temperature continuously variable
- * Flexible connection hoses 3/8"
- * Fastening by means of threaded sleeve M35 x 1.5 (preassembled socket)
- * Mounting hole size Ø35 - 37 mm

Technical Data

Flow rate needle spray
Flow rate normal spray
Connection
Spout
Detachable
Handling
Kitchenspray
Color code
Installation type
Faucet_typ
Measure Height
Acoustic group
Projection A
Energy label
Dimension Water outlet
material

9 l/min (3 bar)
9 l/min (3 bar)
Flexible connection hoses
swivel
detachable
top lever
Pull-out spray
stainless steel
Pillar installation
Lever mixer
280
II
A 220
A
197
stainless steel



Spare Parts



KWC ONO
Lever mixer - Kitchen - detachable

Modell-Linie: **ONO** | **10.151.053.700FL**
Taps | Manual taps



Cartridge M 35 H

538327
Z.537.582

Combination wrench ONO

635392
Z.635.392