



KWC SHOWERCULTURE  
Shower system style

Modell-Linie: **SHOWERCULTURE | 26.006.333.000**  
Showers | Shower Systems



KWC-No.

**124703**  
chromeline, AD150±20, A 400

**3600003736**  
matt black, AD150±20, A400

**3600003726**  
brushed steel, AD150±20, A400

Color\_code

chrome

matt black

brushed steel

- \* Shower system style
- \* EcoProtect - water-saving device
- \* TouchProtect - anti-scald protection thanks to the "double skin" principle
- \* The water-bearing sliding wall bar can be shortened to any individual length as required
- \* Swiveling bracket, shower head with ball joint
- \* SkinProtect - Safety stop prevents scalding
- \* Turning handle to control flow and for diverter
- \* KWC ball joint bracket, elevation adjustment lockable
- \* Tube diameter 20 mm
- \* Intrinsically safe against backflow
- \* Easy to install on existing connections
- \* Thermostatic precision control unit

- constant water temperature (even when mains pressure fluctuates)
- fast response
- \* Wall connections ½" x ¾", without shut-off valve eccentric 10 mm
- \* Scope of delivery:
  - Thermostat incl. wall connections with outlet (top) for water-bearing sliding wall bar
  - Hand shower KWC CHOICE-G 26.000.125.000
  - Shower hose 1600 mm, plastic 26.001.003.000
  - Shower head KWC PIATTO -X R300 26.000.215.000
  - Sliding wall bar kit 26.004.004.000
  - Shower guide rod holder (top), for connecting guide rod and spray arm

Technical Data

Flow rate
Spray outlet: Flow rate
Shower_set
Color_code
Installation_type
Faucet_typ
Dimension Height
G_Acoustic group
Spray outlet: Acoustic group
Projection_A
Connection measure
material

17.8 l/min (3 bar)
11.3 l/min (3bar)
with shower head, hose
chrome
Wall mounted
Thermostatic
1300
I
I
A 400
150+/- 20
Brass

