

KWC DOMO 6.0 Lever mixer - Kitchen

Modell-Linie: DOMO 6.0 | 10.661.003.000FL
Kranar | Hydraulické armatury



KWC-No.

124928

chromeline, A 215, flexible connection hoses

- * Lever mixer
- * Lever installation only possible on the right side
- Child safety: cold water flow in lever position towards the front
- * gap between wall and centre of mounting hole min. 26 mm
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Intrinsicly safe against backflow
- * Pull-out spray
 - SprayClean - easy to clean and actively prevents limescale buildup
 - up to 600 mm pull-out length
 - TripleClean - Normal, soft, and power stream modes
 - hose surface to fit faucet surface
 - QuickConnect - Simple hose connection system

- * Hose guide, swivelling 150°
- * EasyLock - a pull-out spray that easily slides back into place
- * OptimalSpace - ample space for washing or working
- * KWC cartridge M 35 S
 - with ceramic discs
 - flow rate and temperature continuously variable
 - temperature limitation
- * Flexible connection hoses 3/8"
- * QuickInstallation - Fastening via threaded connection with locking screws
- * Mounting hole size $\varnothing 35$ mm
- * To be ordered separately (optional or if necessary):
 - Swivel range limited to 120°, Z.538.320

Technical Data

ATT-KWC-A_AUSZUGBRAUSE_SIEB

ATT-KWC-A_AUSZUGBRAUSE_NORMAL

Connection

ATT-KWC-AUSLAUF

Handling

Kitchen_spray

ATT-KWC-FARBCODE

Installation_type

Faucet_typ

ATT-KWC-BAUFORM

Measure_Height

G_Acoustic group

Projection_A

EnergyLabelCH

ATT-KWC-MASS-WASSERAUSTRITT

Material

8 l/min (3 bar)

8 l/min (3 bar)

Flexible_Anschlusschläuche

schwenkbar

seitenbedient

Auszugbrause

chromeline

Standmontage

Hebelmischer

L-Auslauf

345

I

A215

A

285

Mässing

