


KWC DOMO E Lever mixer - Kitchen

Modell-Linie: DOMO E | 10.701.003.700FL

Taps | Manual taps





KWC-No.

124937

stainless steel, A 215, flexible connection hoses

- * Lever mixer * Lever installation only possible on the right side Child safety: cold water flow in lever position towards the front * gap between wall and centre of mounting hole min. 26 mm * TouchProtect anti-scald protection thanks to the "double skin"

- * Inducinerate anti-scala protection thanks to the aduble sk principle * Intrinsically safe against backflow * Pull-out spray SprayClean easy to clean and actively prevents limescale buildup
- up to 600 mm pull-out length TripleClean Normal, soft, and power stream modes hose surface to fit faucet surface

- QuickConnect Simple hose connection system
 * Hose guide, swivelling 150°
 * EasyLock a pull-out spray that easily slides back into place
 * OptimalSpace ample space for washing or working
 * KWC cartridge M 35 S
 with ceramic discs
 flaw and and comportative continuously wardable

- with ceramic alses flow rate and temperature continuously variable temperature limitation * Flexible connection hoses %" * QuickInstallation Fastening via threaded connection with locking screws * Mounting hole size ø35 mm

Technical Data

Flow rate needle spray	
Flow rate normal spray	
Connection	
Spout	
Handling	
Kitchenspray	
Color code	
Installation type	
Faucet_typ	
Measure Height	
Acoustic group	
Projection A	
Energy label	
Dimension Water outlet	
material	

8 l/min (3 bar)	
8 l/min (3 bar)	
Flexible connection hos	ses
swivel	
side lever	
Pull-out spray	
stainless steel	
Pillar installation	
Lever mixer	
330	
1	
A 215	
В	
285	
stainless steel	

