

# KWC AVA 2.0 Lever mixer - Basin

## Modell-Linie: AVA 2.0 | 12.468.131.000FL

Taps | Manual taps



## KWC-No.

125096 chromeline, A 150, flexible connection hoses, with pop-up valve

### 125097

chromeline, A 150, flexible connection hoses, without pop-up valve

## 125098

chromeline, A 150, flexible connection hoses, with Push Open

- \* Lever installation only possible on the right side Child safety: cold water flow in lever position towards the front \* gap between wall and centre of mounting hole min. 27 mm \* EcoProtect water-saving device \* Swivel court 100°
- \* Swivel spout 120°
- Neoperl® Perlator® SJR, swivelling jet regulator
  \* OptimalSpace ample space for washing or working
- \* KWC cartridge S 25

# 150 27 <u>95</u> 100 67 210 -4°-16 183 ø43 max.45 🖡 M33 ø63 364 1 1/4

### Pop-up\_valve

with pop-up valve

without pop-up valve

with Push open

- with ceramic discs flow rate and temperature continuously variable
- \* Flexible connection hoses 3/8" \* QuickInstallation Fastening via threaded connection with locking

- \* Quickinstaliation Fastening via the screws \* Mounting hole size ø35 mm \* Scope of delivery: KWC pop-up valve Z.538.581.000

### **Technical Data**

Flow rate	
Pop-up_valve	
Connection	
Spout	
Handling	
Color code	
Installation_type	
Faucet_typ	
Dimension Height	
G_Acoustic group	
Projection_A	
Energy Label	
Dimension Water outlet	
material	

5 l/min (3 bar)	
with pop-up valve	
Flexible connection hose	
swivel	
side lever	
chrome	
Pillar installation	
Lever mixer	
210	
I	
A 150	
A	
183	
Brass	

