


## KWC KIO Kitchen - with LED-technology

Modell-Linie: KIO | 10.481.232.176FL  
Umyvadlové armatury | Elektronické armatury



### KWC-No.

**125193**  
chromeline, A 220, flexible connection hoses, mains receiver

**125194**  
matt black, A 220, flexible connection hoses, mains receiver

**125195**  
decor steel, A 220, flexible connection hoses, mains receiver

### ATT-KWC-FARBCODE

chromeline

matt black

decor steel

- \* IntelligentControl - electronic control
- \* gap between wall and centre of mounting hole min. 26 mm
- \* TouchProtect - anti-scald protection thanks to the "double skin" principle
- \* Microprocessor-control
- touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
- with cleaning programme
- \* Pull-out spray ergonomic spout alignment, shape and handling
- SprayClean - easy to clean and actively prevents limescale buildup
- Neoperl® Perlator® laminar
- PowerClean - needle spray mode, with automatic diverter reset
- Integrated control unit

- up to 500 mm pull-out length
- \* Hose guide, swivelling 150°, can be extended to 360°
- \* EasyLock - a pull-out spray that easily slides back into place
- \* OptimalSpace - ample space for washing or working
- \* KWC control unit, maintenance-free
- up-to-date microprocessor and drive technology
- tried-and-tested valve technology
- with-out installation materials
- designed for wired connection to 1 operating unit (standard)
- \* Flexible connection hoses 3/8"
- \* QuickInstallation - Fastening via threaded connection with locking screws
- \* Mounting hole size ø35 mm
- \* Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 12 V / cable length 2000 mm
  - \* To be ordered separately (optional or if necessary):
  - Swivel range limited to 120° Z.538.320

### Technické údaje

A\_Spout\_Spray

10 l/min (3 bar)

ATT-KWC-EL\_STEUERUNG

berührungsarm

ATT-KWC-LICHT

mit LED-Technologie

Connection

Flexible\_Anschlusschläuche

ATT-KWC-AUSLAUF

schwenkbar

ATT-KWC-STROMVERSORGUNG

Netz AP

Handling

frontbedient

Kitchen\_spray

Auszugbrause

ATT-KWC-FARBCODE

matt black

Installation\_type

Standmontage

Faucet\_typ

Hebelmischer

ATT-KWC-BAUFORM


L-Auslauf

Measure\_Height

362

G\_Acoustic group

I



## KWC KIO

Kitchen - with LED-technology

Modell-Linie: KIO | 10.481.232.176FL

Umyvadlové armatury | Elektronické armatury

Projection\_A

A220

EnergyLabelCH

B

ATT-KWC-MASS-WASSERAUSTRITT

230

Materiál

mosaz

### Náhradní díly



#### Wrench to KIO pull-out spray

**538810**

Z.538.810