


KWC KIO Kitchen - with LED-technology

Modell-Linie: KIO | 10.481.232.127FL
Kranar | Elektronické armatury



KWC-No.

125193
chromeline, A 220, flexible connection hoses, mains receiver

125194
matt black, A 220, flexible connection hoses, mains receiver

125195
decor steel, A 220, flexible connection hoses, mains receiver

ATT-KWC-FARBCODE

chromeline

matt black

decor steel

- * IntelligentControl - electronic control
- * gap between wall and centre of mounting hole min. 26 mm
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Microprocessor-control
- touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
- with cleaning programme
- * Pull-out spray ergonomic spout alignment, shape and handling
- SprayClean - easy to clean and actively prevents limescale buildup
- Neoperl® Perlator® laminar
- PowerClean - needle spray mode, with automatic diverter reset
- Integrated control unit

- up to 500 mm pull-out length
- * Hose guide, swivelling 150°, can be extended to 360°
- * EasyLock - a pull-out spray that easily slides back into place
- * OptimalSpace - ample space for washing or working
- * KWC control unit, maintenance-free
- up-to-date microprocessor and drive technology
- tried-and-tested valve technology
- with-out installation materials
- designed for wired connection to 1 operating unit (standard)
- * Flexible connection hoses 3/8"
- * QuickInstallation - Fastening via threaded connection with locking screws
- * Mounting hole size ø35 mm
- * Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 12 V / cable length 2000 mm
- * To be ordered separately (optional or if necessary):
 - Swivel range limited to 120° Z.538.320

Technical Data

A_Spout_Spray

10 l/min (3 bar)

ATT-KWC-EL_STEUERUNG

berührungsarm

ATT-KWC-LICHT

mit LED-Technologie

Connection

Flexible_Anschlusschläuche

ATT-KWC-AUSLAUF

schwenkbar

ATT-KWC-STROMVERSORGUNG

Netz AP

Handling

frontbedient

Kitchen_spray

Auszugbrause

ATT-KWC-FARBCODE

decor steel

Installation_type

Standmontage

Faucet_typ

Hebelmischer

ATT-KWC-BAUFORM


L-Auslauf

Measure_Height

362

G_Acoustic group

I



KWC KIO

Kitchen - with LED-technology

Modell-Linie: KIO | 10.481.232.127FL
Kranar | Elektronické armatury

Projection_A	A220
EnergyLabelCH	B
ATT-KWC-MASS-WASSERAUSTRITT	230
Material	Mässing

Reservdelar



Wrench to KIO pull-out spray

538810
Z.538.810