


KWC VITA PRO 2.0 Lever mixer - Basin

Modell-Linie: VITA PRO 2.0 | 11.522.203.000

Kranar | Hydraulické armatury





KWC-No.

125232

chromeline, AD 153 +/- 8 mm, A 175

125233

chromeline, AD 153 +/- 8 mm, A 225

- * Lever mixer
- * Operation designed for a secure grip, as well as safe and easy
- handling
 * Ergonomic and robust operating lever, made of polyamide
- to adjust the handling even better to suit personal requirements, the offset lever can be installed so that it is twisted into the cap (standard: see illustration)
- * EcoProtect water-saving device * Swivel spout 90°
- adjustable with screw

Projection_A

A175

A225

- Neoperl® Perlator® laminar

 * OptimalSpace ample space for washing or working

 * KWC cartridge with safety device M 35 OP

 with ceramic discs

- flow rate and temperature continuously variable temperature limitation
- Reinforced stopper for output volume and temperature (standard setting) * Wall connections $\frac{1}{2}$ " x $\frac{1}{2}$ ", without shut-off valve L 40 eccentric 4
- mm

Technical Data

| A_Spout_Spray | |
|-----------------------------|---|
| ATT-KWC-AUSLAUF | |
| - Handling | |
| ATT-KWC-FARBCODE | |
| Installation_type | |
| Faucet_typ | |
| Measure_Height | |
| G_Acoustic group | |
| Projection_A | |
| Connection measure | |
| ATT-KWC-MASS-WASSERAUSTRITT | |
| Material | • |

| 5.8 l/min (3 bar) | | |
|-------------------|--|--|
| schwenkbar | | |
| frontbedient | | |
| chromeline | | |
| Väggmontering | | |
| Hebelmischer | | |
| 140 | | |
| I | | |
| A225 | | |
| 153+/-8 | | |
| 69 | | |
| Mässing | | |





