


KWC IQUA
Automatic, non-contact - Basin

Modell-Linie: IQUA | 12.696.151.000
Taps | Self closing taps



KWC-No.

125257
chromeline, A 115, flexible connection hose, without pop-up valve, battery, Basic, without mixing

125258
chromeline, A 115, flexible connection hose, without pop-up valve, mains receiver, Basic, without mixing

- * Automatic controled design
- * Infrared sensor L20
- * Without mixing
- for cold or mixed water supply
- * EcoProtect - water-saving device
- * Basic: counter-sunk iqua-click
- * Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration
- 12- or 24-hour-hygiene flushing activatable

Technical Data

Flow rate
Pop-up_valve
Electronical_control
Connection
Spout
IQUA_Click
Power_supply
Color_code
Installation_type
Faucet_typ
Dimension Height
G_Acoustic group
Projection_A
Energy Label
Dimension Water outlet
material

Power_supply

battery
mains receiver

- * Fixed spout
- Neoperl® Cascade®
- * Electrovalve
- * Flexible connection hose 3/8"
- * Fastening by means of stud bolt M8 x 1
- * Mounting hole size ø35 mm
- * Scope of delivery:
- Battery 6 V Lithium CRP2
- lifespan at 100 circuits/day: 4 years
- 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

6 l/min (3 bar)
without pop-up valve
Automatic, non-contact
Flexible connection hose
fixed
Basic, without mixing
battery
chrome
Pillar installation
Electronic
140
I
A 115
A
82
Brass

