


KWC IQUA

Automatic, non-contact - Basin

Modell-Linie: IQUA | 12.696.171.000

Taps | Self closing taps





KWC-No.

chromeline, A 115, flexible connection hose, without pop-up valve, battery, Basic, without mixing

chromeline, A 115, flexible connection hose, without pop-up valve, mains receiver, Basic, without mixing

- * Automatic controled style * Infrared sensor L20

- * Without mixing
 for cold or mixed water supply
 * EcoProtect water-saving device
 * Basic: counter-sunk iqua-click
 * Microprocessor-control

- flow time adjustable (1 second factory setting)
 short time off (cleaning) activatable
 continuous water flow (filling) activatable
 sensor sensitivity adjustable permanent, automatic selfcalibration
 - 12- or 24-hour-hygiene flushing activatable

Power_supply

battery

- * Fixed spout Neoperl® Cascade®
- * Electrovalve * Flexible connection hose %"
- * Fastening by means of stud bolt M8 x 1 * Mounting hole size ø35 mm * Scope of delivery:

- Battery 6 V Lithium CRP2 lifespan at 100 circuits/day: 4 years
- A Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

Technical Data

Flow rate	
Pop-up_valve	
Electronical_control	
Connection	
Spout	
IQUA_Click	
Power_supply	
Color_code	
Installation_type	
Faucet_typ	
Dimension Height	
G_Acoustic group	
Projection_A	
Energy Label	
Dimension Water outlet	
material	<u> </u>

6 l/min (3 bar)	
without pop-up valve	
Automatic, non-contact	
Flexible connection hose	
fixed	
Basic, without mixing	
battery	
chrome	
Pillar installation	
Electronic	
140	
1	
A 110	
А	
66	
Brass	



