


KWC IQUA  
Automatic, non-contact - Basin

Modell-Linie: IQUA | 12.696.091.000  
Taps | Self closing taps



KWC-No.

**125279**  
chromeline, A 115, flexible connection hose, without pop-up valve, battery, Basic, with mixing

**125280**  
chromeline, A 115, flexible connection hose, without pop-up valve, mains receiver, Basic, with mixing

- \* Automatic controled style
- \* Infrared sensor L10
- \* With mixing
- temperature limiter adjustable
- \* EcoProtect - water-saving device
- \* Basic: counter-sunk iqua-click
- \* Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration

Power supply

battery

mains receiver

- 12- or 24-hour-hygiene flushing activatable
- \* Fixed spout
- Neoperl® Cascade®
- \* Electrovalve
- \* Flexible connection hoses 3/8"
- \* Fastening by means of stud bolt M8 x 1
- \* Mounting hole size 35 mm
- \* Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 6 V
- 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

Technical Data

Flow rate
pop-up valve
Electronical control
Connection
Spout
IQUA-Click
Power supply
Color code
Installation type
Faucet_typ
Measure Height
Acoustic group
Projection A
Energy label
Dimension Water outlet
material

6 l/min (3 bar)
without pop-up valve
Automatic, non-contact
Flexible connection hose
fixed
Basic, with mixing
mains receiver
chromeline
Pillar installation
Electronic
140
I
A 110
A
66
Brass

