


KWC

Trim kit, with safety device DIN EN 1717 – Thermostatic mixer – Tub

Modell-Linie: SHOWERCULTURE | 20.004.853.000

Showers | Exposed bath mixer





KWC-No.

125300

chromeline, trim kit, with safety device DIN EN 1717

125301

matt black, trim kit, with safety device DIN EN 1717

125302

brushed steel, trim kit, with safety device DIN EN 1717

- $\mbox{\ensuremath{^{\star}}}\mbox{\ensuremath{\text{Trim}}}\mbox{\ensuremath{\text{kit}}}\mbox{\ensuremath{\text{with}}}\mbox{\ensuremath{\text{thermostatic}}}\mbox{\ensuremath{\text{clustic}}}\mbox{\ensurema$
- with integrated hose connection with ON/OFF push-button CHOICE with flow regulator
 - above or below for second consumer with ON/OFF push-button
- CHOICE
 * SkinProtect Safety stop prevents scalding
- * Intrinsically safe against backflow

Color code

chromeline

matt black

brushed steel

- * Scope of delivery: Thermostatic mixer unit
- Diverter unit

- Diverter unit
 Hose connection unit with ON/OFF push-button and flow regulator
 Fastening of the cover plate without screws
 * To be ordered separately:
 Unit for concealed installation NWC HOMEBOX Thermostatic/ lever mixer 2 consumers 39.006.261.931



Technical Data

Flow rate	
Spray outlet: Flow rate	
Diameter	
Color code	
Installation type	
Faucet_typ	
Acoustic group	
Concealed unit	
Spray outlet: Acoustic group	
Energy label	
material	

19.5 l/min (3bar)	
14 l/min (3bar)	
362 x 100	
chromeline	
Wall mounted	
Thermostatic	
II	
Trim kit, with vacuum breaker	
ſ	
С	
Brass	



