


# **KWC**

Trim kit, with safety device DIN EN 1717 – Thermostatic mixer – Tub

# Modell-Linie: SHOWERCULTURE | 20.004.853.177

Showers | Exposed bath mixer





# KWC-No.

### 125300

chromeline, trim kit, with safety device DIN EN 1717

### 125301

matt black, trim kit, with safety device DIN EN 1717

# 125302

brushed steel, trim kit, with safety device DIN EN 1717

- $\mbox{\ensuremath{^{\star}}}\mbox{\ensuremath{\text{Trim}}}\mbox{\ensuremath{\text{kit}}}\mbox{\ensuremath{\text{with}}}\mbox{\ensuremath{\text{thermostatic}}}\mbox{\ensuremath{\text{function}}}\mbox{\ensuremath{\text{unit}}}\mbox{\ensuremath{\text{KWC}}}\mbox{\ensuremath{\text{HOMEBOX}}}\mbox{\ensuremath{\text{*}}}\mbox{\ensuremath{\text{Chomebox}}}\mbox{\ensuremath{\text{*}}}\mbox{\ensuremath{\text{chomebox}}}\mbox{\ensuremath{\text{chomebox}}}\mbox{\ensuremath{\text{*}}}\mbox{\ensuremath{\text{chomebox}}}\mbox{\ensuremath{\text{chomebox}}}\mbox{\ensuremath{\text{with}}}\mbox{\ensuremath{\text{chomebox}}}\mbox{\ensuremath{$
- with integrated hose connection with ON/OFF push-button CHOICE with flow regulator
  - above or below for second consumer with ON/OFF push-button
- CHOICE
  \* SkinProtect Safety stop prevents scalding
- \* Intrinsically safe against backflow

### Color code

chromeline

matt black

brushed steel

- \* Scope of delivery: Thermostatic mixer unit
- Diverter unit

- Diverter unit
   Hose connection unit with ON/OFF push-button and flow regulator
   Fastening of the cover plate without screws
  \* To be ordered separately:
   Unit for concealed installation NWC HOMEBOX Thermostatic/ lever mixer 2 consumers 39.006.261.931



# **Technical Data**

Flow rate	
Spray outlet: Flow rate	
Diameter	
Color code	
Installation type	
Faucet_typ	
Acoustic group	
Concealed unit	
Spray outlet: Acoustic group	
Energy label	
material	

19.5 l/min (3bar)	
14 l/min (3bar)	
362 x 100	
brushed steel	
Wall mounted	
Thermostatic	
II	
Trim kit, with vacuum breaker	
I	
С	
Brass	



