


KWC AVA 2.0

Lever mixer - Kitchen

Modell-Linie: AVA 2.0 | 10.461.032.000FL

Taps | Manual taps





KWC-No.

125364

chromeline, A 220, flexible connection hoses

125365

matt black, A 220, flexible connection hoses

125366

brushed steel, A 220, flexible connection hoses

- $\mbox{\ensuremath{^{\star}}}\mbox{\ensuremath{\text{TouchProtect}}}\mbox{\ensuremath{\text{Protect}}}\mbox{\ensuremath{\text{-}}}\mbox{\ensuremath{\text{anti-scald}}}\mbox{\ensuremath{\text{protection}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{TouchProtect}}}\mbox{\ensuremath{\text{-}}}\mbox{\ensuremath{\text{chanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{shanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{}}\mb$

- principle
 * Intrinsically safe against backflow
 * Pull-out spray
 SprayClean easy to clean and actively prevents limescale - up to 600 mm pull-out length - TripleClean - Normal, soft, and power stream modes - hose surface to fit faucet surface - QuickConnect - Simple hose connection system

Color code

matt black

brushed steel

- * Hose guide, swivelling 120°
 * EasyLock a pull-out spray that easily slides back into place
 * KWC cartridge M 35 S
 with ceramic discs

- flow rate and temperature continuously variable

- temperature limitation * Flexible connection hoses %" * QuickInstallation Fastening via threaded connection with locking screws * Mounting hole size ø35 mm

Technical Data

recillical Data	
Flow rate needle spray	
Flow rate normal spray	
Connection	
Spout	
Handling	
Kitchen_spray	
Color code	
Installation_type	
Faucet_typ	
Dimension Height	
G_Acoustic group	
Projection_A	
Energy Label	
Dimension Water outlet	
material	

9 l/min (3 bar)	
8 l/min (3 bar)	
Flexible connection hoses	
swivel	
top lever	
Pull-out spray	
chrome	
Pillarinstallation	
Lever mixer	
236	
1	
A 220	
В	
141	
Brass	













