


KWC AVA 2.0

Lever mixer - Kitchen

Modell-Linie: AVA 2.0 | 10.461.032.177FL

Taps | Manual taps





KWC-No.

125364

chromeline, A 220, flexible connection hoses

125365

matt black, A 220, flexible connection hoses

125366

brushed steel, A 220, flexible connection hoses

- $\mbox{\ensuremath{^{\star}}}\mbox{\ensuremath{\text{TouchProtect}}}\mbox{\ensuremath{\text{Protect}}}\mbox{\ensuremath{\text{-}}}\mbox{\ensuremath{\text{anti-scald}}}\mbox{\ensuremath{\text{protection}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{to}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{TouchProtect}}}\mbox{\ensuremath{\text{-}}}\mbox{\ensuremath{\text{chanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{shanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{\text{thanks}}}\mbox{\ensuremath{}}\mb$

- principle
 * Intrinsically safe against backflow
 * Pull-out spray
 SprayClean easy to clean and actively prevents limescale up to 600 mm pull-out length

 TripleClean - Normal, soft, and power stream modes
 hose surface to fit faucet surface

- QuickConnect Simple hose connection system

Color code

matt black

brushed steel

- * Hose guide, swivelling 120°
 * EasyLock a pull-out spray that easily slides back into place
 * KWC cartridge M 35 S
 with ceramic discs

- flow rate and temperature continuously variable

- temperature limitation * Flexible connection hoses %" * QuickInstallation Fastening via threaded connection with locking screws * Mounting hole size ø35 mm

Tankai ani Data

Flow rate needle spray			
Flow rate normal spray			
Connection			
Spout			
Handling			
Kitchen_spray			
Color code			
Installation_type			
Faucet_typ			
Dimension Height			
G_Acoustic group			
Projection_A			
Energy Label	_	•	
Dimension Water outlet			
material			

9 l/min (3 bar)	
8 l/min (3 bar)	
Flexible connection hoses	
swivel	
top lever	
Pull-out spray	
brushed steel	
Pillar installation	
Lever mixer	
236	
I	
A 220	
В	
141	
Brass	











