


KWC BISTRO E

Lever mixer – Kitchen

Modell-Linie: BISTRO E | 10.581.433.700FL

Taps | Manual taps





KWC-No.

stainless steel, A 235, flexible connection hoses

- * Lever mixer

 * HighFlex patented spring hose technology

 * Lever installation only possible on the right side

 Child safety: cold water flow in lever position towards the front

 * TouchProtect anti-scald protection thanks to the "double skin" principle
 *Spray
 - SprayClean - easy to clean and actively prevents limescale

- buildup

 Neoperl® Caché® SSR, swivelling jet regulator

 PowerClean needle spray mode, with automatic diverter reset

* EasyLock - a pull-out spray that easily slides back into place * Swivel spout 360° * OptimalSpace - ample space for washing or working * KWC cartridge M 35 S - with ceramic discs

- flow rate and temperature continuously variable
- * Flexible connection hoses %"

 * QuickInstallation Fastening via threaded connection with locking screws
 * Mounting hole size ø35 mm



Technical Data

| Flow rate | |
|------------------------|---|
| Spray: Flow rate | |
| Connection | |
| Spout | |
| Handling | |
| Kitchen_spray | |
| Color code | |
| Installation_type | |
| Faucet_typ | |
| Design | |
| Dimension Height | |
| G_Acoustic group | |
| Projection_A | · |
| Energy Label | · |
| Dimension Water outlet | |
| material | |

| 8 l/min (3 bar) |
|---------------------------|
| 6.4 l/min (3 bar) |
| Flexible connection hoses |
| swivel |
| side lever |
| Diverter spray |
| stainless steel |
| Pillar installation |
| Lever mixer |
| J-Spout |
| 459 |
| |
| A 235 |
| A |
| 180 |
| stainless steel |











