


KWC BISTRO E

Lever mixer – Kitchen

Modell-Linie: BISTRO E | 10.581.144.700FL

Taps | Dishwashing





KWC-No.

stainless steel, A 295, flexible connection hoses

- * Lever mixer
 * Suspension spring
 * TouchProtect anti-scald protection thanks to the "double skin"

- * TouchProtect anti-scald protection thanks to the "double skin" principle
 * Intrinsically safe against backflow and cross flow
 * Swivel spout
 Neoperl® Caché® laminar
 * Pre-rinse spray
 with integrated delayed closing device to minimize water hammer with valve maintenance unit for cleaning
 SprayLock lockable jet spray

- PowerClean needle spray mode
- Towarded relative spray mode
 2 jet types
 OptimalSpace ample space for washing or working
 KWC cartridge M 35 S
 with ceramic discs

- flow rate and temperature continuously variable

 * Flexible connection hoses %"

 * QuickInstallation Fastening via threaded connection with locking screws
 * Mounting hole size ø35 mm

Technical Data

Flow rate	
Flow rate normal spray	
Spray: Flow rate	
Connection	
Spout	
Handling	
Kitchenspray	
Color code	
Installation type	
Faucet_typ	
Measure Height	
Acoustic group	
Spray outlet: Acoustic group	
Projection A	
Energy label	
Dimension Water outlet	
material	

14 l/min (3 bar)	
4 l/min (3bar)	
8 l/min (3 bar)	
Flexible connection hoses	
swivel	
side lever	
Pre-rinse spray	
stainless steel	
Pillar installation	
Lever mixer	
820	
II	
1	
A 295	
С	
190/290	
stainless steel	















KWC BISTRO E Lever mixer – Kitchen

Modell-Linie: BISTRO E | 10.581.144.700FL Taps | Dishwashing



Service key Neoperl © Caché ©, STD, 24 mm, grey

635231 Z.635.231