


KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.122.700FL





KWC-No.

stainless steel, A 125, flexible connection hose, without drain fitting, surface-mounted power supply unit, without mixing

- * Automatic, non-contact, basin opto-electronic controlled * Made of stainless steel * Without mixing for cold or mixed water supply
- * EcoProtect water-saving device * Control electronics

- 24-hour hygiene flushing adjustable Safety shutdown in case of continuous reflection Storage of statistical data
- * Fixed spout

- Neoperl® Perlator® SSR, swivelling jet regulator
 * Electrovalve
 * Flexible connection hose 3/8"
 * QuickInstallation Fastening via threaded connection M33 x 1.5
 with locking screws
 * Mounting hole size 325 pers



- with locking screws

 * Mounting hole size ø35 mm

 * Scope of delivery:
 Mains receiver 100-240 V AC 6.75 V DC

 * Order separately (optional or if required):
 Possibility of parameterization via bidirectional remote control, or C-module Z.540.137 with an app

Technical Data

Flow rate	
Electronical control	
Connection	
Spout	
Power supply	
Color code	
Installation type	
Faucet_typ	
Acoustic group	
Projection A	
Energy label	
•	

4.8 l/min (3 bar)		
Automatic, non-contact		
Pressure Balance1		
fixed		
mains receiver		
stainless steel		
Pillarinstallation		
Electronic		
I		
A 125		
A		





Optional Accessories



KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.122.700FL Taps | Electronic taps







Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

C module

3600001331 ACEX9020