


## KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.122.700FL

Taps | Electronic taps



### KWC-No.

**360001582**

stainless steel, A 125, flexible connection hose, without drain fitting, surface-mounted power supply unit, without mixing

- \* Automatic, non-contact, basin
- opto-electronic controlled
- \* Made of stainless steel
- \* Without mixing
- for cold or mixed water supply
- \* EcoProtect - water-saving device
- \* Control electronics
- 24-hour hygiene flushing adjustable
- Safety shutdown in case of continuous reflection
- Storage of statistical data
- \* Fixed spout

- Neoperl® Perlator® SSR, swivelling jet regulator
- \* Electrovalve
- \* Flexible connection hose 3/8"
- \* QuickInstallation - Fastening via threaded connection M33 x 1.5 with locking screws
- \* Mounting hole size ø35 mm
- \* Scope of delivery:
- Mains receiver 100-240 V AC - 6.75 V DC
- \* Order separately (optional or if required):
- Possibility of parameterization via bidirectional remote control, or C-module Z.540.137 with an app

NEW

### Technical Data

Flow rate
Electronical control
Connection
Spout
Power supply
Color code
Installation type
Faucet_typ
Acoustic group
Projection A
Energy label

4.8 l/min (3 bar)
Automatic, non-contact
Pressure Balance1
fixed
mains receiver
stainless steel
Pillar installation
Electronic
I
A 125
A



### Optional Accessories

## KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.122.700FL

Taps | Electronic taps



**Bidirectional remote control for  
electronical fittings F3 and F5**

---

**2030036654**  
ACEX9005

---



**2-button remote control for fittings F3  
and F5**

---

**2030036849**  
ACEX9004

---