


KWC ONO E Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.012.700FL

Taps | Electronic taps





KWC-No.

3600001583

stainless steel, A 125, flexible connection hoses, without drain fitting, battery, with mixing

- * Automatic, non-contact, basin opto-electronic controlled * Made of stainless steel * With mixing adjustable, twist-proof temperature stop * EcoProtect water-saving device * Control electronics 2.4 hoir suprising adjustable

- 24-hour hygiene flushing adjustable
 Safety shutdown in case of continuous reflection

- Storage of statistical data * Fixed spout Neoperl® Perlator® SSR, swivelling jet regulator

Technical Data

Flow rate	4.8 l/min (3 bar)
Electronical_control	Automatic, non-contact
Connection	Spare parts1
Spout	fixed
Power_supply	battery
Color code	stainless steel
Installation_type	Pillar installation
Faucet_typ	Electronic
Dimension Height	165
G_Acoustic group	
Projection_A	A 125
Energy Label	A

Optional Accessories

- * Electrovalve * Flexible connection hoses 3/8"

- * Flexible connection noses 3/8"
 * QuickInstallation Fastening via threaded connection M33 x 1.5 with locking screws
 * Mounting hole size ø35 mm
 * Scope of delivery:
 Battery compartment including battery 6V Lithium CRP2 for menutine under the wachbracin
- Battery Comparison in the main and any battery of Ethilding CAP2 for mounting under the washbasin
 Order separately (optional or if required):
 Possibility of parameterization via bidirectional remote control, or C-module (3600001331) with an app

NEW





KWC ONO E Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.012.700FL Taps | Electronic taps





Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

C module

3600001331 ACEX9020