


KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.012.700FL





KWC-No.

stainless steel, A 125, flexible connection hoses, without drain fitting, battery, with mixing

- * Automatic, non-contact, basin
 opto-electronic controlled
 * Made of stainless steel
 * With mixing
 adjustable, twist-proof temperature stop
 * EcoProtect water-saving device
 * Control electronics

- 24-hour hygiene flushing adjustable Safety shutdown in case of continuous reflection

- Storage of statistical data * Fixed spout Neoperl® Perlator® SSR, swivelling jet regulator

- * Electrovalve

 * Flexible connection hoses 3/8"

 * QuickInstallation Fastening via threaded connection M33 x 1.5

 with locking screws

 * Mounting hole size ø35 mm

 * Scope of delivery:

 Battery compartment including battery 6V Lithium CRP2 for mounting under the was phasin

- *Order separately (optional or if required):
 Possibility of parameterization via bidirectional remote control, or C-module (3600001331) with an app



Technical Data

Flow rate		
Electronical control		
Connection		
Spout		
Power supply		
Color code		
Installation type		
Faucet_typ		
Measure Height		
Acoustic group		
Projection A		
Energy label		

4.8 l/min (3 bar)	
Automatic, non-contact	
Spare parts 1	
fixed	
battery	
stainless steel	
Pillar installation	
Electronic	
165	
T	
A 125	
A	







Optional Accessories



KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.012.700FL Taps | Electronic taps





Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004