


KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.022.700FL





KWC-No.

stainless steel, A 125, flexible connection hoses, without drain fitting, surface-mounted power supply unit, with mixing

- * Automatic, non-contact, basin
 opto-electronic controlled
 * Made of stainless steel
 * With mixing
 adjustable, twist-proof temperature stop
 * EcoProtect water-saving device
 * Control electronics

- 24-hour hygiene flushing adjustable Safety shutdown in case of continuous reflection Storage of statistical data
- * Fixed spout

- Neoperl® Perlator® SSR, swivelling jet regulator
 * Electrovalve
 * Flexible connection hoses 3/8"
 * QuickInstallation Fastening via threaded connection M33 x 1.5
 with locking screws
 * Mounting holes in a 25 mer.

- with locking screws

 * Mounting hole size ø35 mm

 * Scope of delivery:
 Mains receiver 100-240 V AC 6.75 V DC

 * Order separately (optional or if required):
 Possibility of parameterization via bidirectional remote control, or
 C-module (3600001331) with an app

Technical Data

Electronical control	
Connection	
Spout	
Power supply	
Color code	
Installation type	
Faucet_typ	
Measure Height	
Projection A	

Automatic, non-contact	
Spare parts1	
fixed	
mains receiver	
stainless steel	
Pillar installation	
Electronic	
165	
A 125	



NEW



Optional Accessories







KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.022.700FL Taps | Electronic taps

Bidirectional remote control for electronical fittings F3 and F5

2-button remote control for fittings F3 and F5

2030036654 ACEX9005

2030036849 ACEX9004