


KWC ONO E Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.023.700FL

Taps | Electronic taps





KWC-No.

3600001588

stainless steel, A 180, flexible connection hoses, without drain fitting, surface-mounted power supply unit, with mixing

- * Automatic, non-contact, basin opto-electronic controlled * For top-mounted basins * Made of stainless steel

- * With mixing
- adjustable, twist-proof temperature stop * EcoProtect water-saving device

- * Control electronics
 * Control electronics
 * 24-hour hygiene flushing adjustable
 * Safety shutdown in case of continuous reflection
 * Storage of statistical data
 * Fixed spout

NEW

- Neoperl® Perlator® SSR, swivelling jet regulator * Electrovalve * Flexible connection hoses 3/8" * QuickInstallation Fastening via threaded connection M33 x 1.5 with locking screws * Mounting hole size c25 mm

- with locking screws * Mounting hole size ø35 mm * Scope of delivery: Mains receiver 100-240 V AC 6.75 V DC * Order separately (optional or if required): Possibility of parameterization via bidirectional remote control, or C-module Z.540.137 with an app

Technical Data

| Flow rate | 4.8 l/min (3 bar) | |
|----------------------|------------------------|--|
| Electronical control | Automatic, non-contact | |
| Connection | Spare parts1 | |
| Spout | fixed | |
| Power supply | mains receiver | |
| Color code | stainless steel | |
| Installation type | for top-mounted sinks | |
| Faucet_typ | Electronic | |
| Dimension Height | 295 | |
| Acoustic group | 1 | |
| Projection A | A 180 | |
| Energy label | A | |

Optional Accessories



KWC ONO E Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.023.700FL Taps | Electronic taps





Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

C module

3600001331 ACEX9020