


KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.023.700FL





KWC-No.

stainless steel, A 180, flexible connection hoses, without drain fitting, surface-mounted power supply unit, with mixing

- * Automatic, non-contact, basin opto-electronic controlled * For top-mounted basins * Made of stainless steel

- * With mixing
- adjustable, twist-proof temperature stop * EcoProtect water-saving device

- * Control electronics
 * 24-hour hygiene flushing adjustable
 * Safety shutdown in case of continuous reflection
 * Storage of statistical data
 * Fixed spout

- Neoperl® Perlator® SSR, swivelling jet regulator
 * Electrovalve
 * Flexible connection hoses 3/8"
 * QuickInstallation Fastening via threaded connection M33 x 1.5
 with locking screws
 * Mounting holes in a 25 mer.

- with locking screws

 * Mounting hole size ø35 mm

 * Scope of delivery:
 Mains receiver 100-240 V AC 6.75 V DC

 * Order separately (optional or if required):
 Possibility of parameterization via bidirectional remote control, or C-module Z.540.137 with an app



Technical Data

Flow rate	
Electronical control	
Connection	
Spout	
Power supply	
Color code	
Installation type	
Faucet_typ	
Measure Height	
Acoustic group	
Projection A	
Energy label	

4.8 l/min (3 bar)	
Automatic, non-contact	
Spare parts1	
fixed	
mains receiver	
stainless steel	
for top-mounted sinks	
Electronic	
295	
ſ	
A 180	
A	









KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.023.700FL Taps | Electronic taps





Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

2-button remote control for fittings F3 and F5

2030036849 ACEX9004