


KWC

Modell-Linie: FIT | 12.548.632.176FL Taps | Manual taps





Pop-up_valve

with Push open

with pop-up valve

without pop-up valve

KWC-No.

125419

chromeline, A 140, flexible connection hoses, with pop-up valve

125420

chromeline, A 140, flexible connection hoses, without pop-up valve

3600008630 matt black, A 140, flexible connection hoses, with Push Open

* Lever mixer * CoolFix - Cold water flow with a centered lever

* Cool HX - Cold water flow with a ce * EcoProtect - water-saving device * Fixed spout - Neoper(® Perlator® * KWC cartridge M 35 OP - with ceramic discs

Technical Data

Flow rate	5 l/min (3 bar)
Pop-up_valve	with Push open
Connection	Flexible connect
Spout	fixed
Handling	top lever
Color_code	matt black
Installation_type	Pillar installation
Faucet_typ	Lever mixer
Dimension Height	164
Energysaving	Coolfix
G_Acoustic group	I
Projection_A	A 140
Energy Label	А
Dimension Water outlet	108
material	Brass

5 l/min (3 bar)	
with Push open	
Flexible connection hoses	
fixed	
top lever	
matt black	
Pillar installation	
Lever mixer	
164	
Coolfix	
A 140	
A	
108	
Brass	

flow rate and temperature continuously variable
temperature limitation
* Flexible connection hoses 3/8"
* Fastening by means of stud bolt M8 x 1
* Mounting hole size ø35 mm
* Scope of delivery:
KWC pop-up valve Push Open 2 in 1 Z.538.321.176

NEW

KWC Group AG | Home: info@kwc.com| Professional: kwc-export.int@kwc.com | www.kwc.com